

# Keypress

written by js | 2022-07-03

## python.py

### Windows

```
import msvcrt as leKeyboard
keypress = leKeyboard.getch()
print (ord(keypress))
```

### Linux

```
import getch as leKeyboard
keypress = leKeyboard.getch()
print (ord(keypress))
```

### Samoodređenje

```
# -*- coding: utf-8 -*-
from sys import platform
from unittest import case
if platform == "linux": import getch as leKeyboard
if platform == "win32": import msvcrt as leKeyboard
keypress = leKeyboard.getch()
skenKod = ( ord (keypress) )
if skenKod in { 224 , 0 , 27 }:
    keypress = leKeyboard.getch()
    skenKod = ord (keypress)          # Win32 - 75:Lijevo 72:Gore
77:Desno 80:Dolje 13:Enter 9:TAB 8:BackSpace
    if skenKod == 91:                # =[ =Linux
        keypress = leKeyboard.getch() # Linux - 68:Lijevo 65:Gore
67:Desno 66:Dolje 10:Enter 9:TAB 127:BackSpace
    skenKod = ord (keypress)
print( skenKod )
```

---

read xread input xinput key character xkey xcharacter press xpress single xsingle  
user userinput xuser xuserinput no enter without enter noenter withoutenter xno  
xwithout xenter one xone cursor arrow keys arrowkeys xcursor xarrow keys  
xarrowkeys